



PRODUCT SPECIFICATION

DESCRIPTION- Q-Lite Pre-Stretched Film

A Pre-Stretched film for pallet wrapping either by hand or on mechanised pallet wrap machines.

NOMINAL DIMENSIONAL CHARACTERISTICS

WIDTH	400mm	To order + / - 5mm
LENGTH	600(m)	To order At least stated length
GAUGE	(mu)	to order + / - 10 %(Gravimetric Average)
DENSITY	(gm/cc)	0 - 92 +/- 0.5%

TYPICAL FILM PROPERTIES

		<u>Test Method</u>	
Micron (mu)	7	ISO 4593:1993	
Puncture Force (N)	12.1	Federal Test Method 2065 101C	
Dart Impact (gms)	136	BS2782	Method 352D
Elmendorf (N)			
Transverse	3.5	BS2782	Method 360A
Machine	0.6		
Tensile strength at break (MPa)			
Machine	24.7	ASTM D882	
Transverse	57.0		

Every endeavour has been made to ensure that the information given herein is true and reliable but is given only for guidance for our customers without any guarantee.

This film is not for use in direct contact with food
 All Blown Film is made of LLDPE (Linear Low Density Polyethylene).
 This film was manufactured using only virgin polymers; no recycled material is used during the manufacturing process although the finished product is recyclable but not bio-degradable.

Users are advised to confirm the suitability of our recommendation by their own tests. Source: Rapra